

Advanced video technology lets you focus on protecting what's most important.

Whether it be challenging outdoor environments or discreet locations, Vicon offers an assortment of high-quality surveillance cameras designed to meet every industry's needs. Our cameras incorporate features such as edge-based analytics to ensure that critical events can be quickly investigated and resolved.

HD video imaging and True WDR deliver exceptional image clarity, which is a key component while reviewing video footage. When combined with accompanying analytics we have meticulously developed, these cameras are transformed into dependable and valuable tools when having to make crucial choices.





NEXT GENERATION CAMERAS FOR ANY ENVIRONMENT

Superior protection when it's needed the most.

When you depend on reliable detection, you can count on Vicon. We have developed a broad range of security cameras to support any mission-critical application. Even in the most demanding environments, we maximize your choice of security options so you can best protect people, properties and assets.

High-Performance Surveillance Cameras

IP Fixed Dome Cameras	4-5
Turret Cameras	6
Bullet Cameras	6-7
Cell Camera	8
IP PTZ Dome Cameras	8-10
Analog Cameras (PTZ, Dome, Bullet or Box)	10-11



Product Details VANDAL DOME SERIES Key Features 2 MP, 4 MP and 5 MP models Models: • H.264/H.265 compression V942D-W312MIR • Min. Illumination: up to 0.01 lux (color) V942D-W310MIR-XW • Temp: -40-140° F (-40-60° C) V942D-W310MIR-XS • True WDR V944D-W312MIR MFZ lenses V945D-W310MIR • Smart IR Illumination; 98 ft (30 m) • Museum Search Smart Encoding These rugged outdoor cameras are • Alarm and Audio input/output ideal in challenging environments. · High Dynamic Range and Starlight ultra-high sensitivity options • Powered by PoE; 12 VDC; 24 VAC • SD card slot for on-camera storage

Key Features Product Details VANDAL DOME SERIES with advanced Al-based analytics • 2 MP, 4 MP, 5 MP and 4K (8 MP) models Models: V982D-W312MIR • H.264/H.265 and M-JPEG compression V984D-W312MIR • Min. Illumination: up to 0.03 lux (color) V985D-W311MIR • Temp: -4-122° F (-20-50° C) V988D-W311MIR • True WDR • MFZ lens • IR Illumination; 90 ft (30 m) Advanced Analytics • Museum Search These dome cameras, with resolutions Quad streaming up to 4K, deliver sharper images while • Audio and Alarm input/output providing a broad range of coverage • Powered by PoE; 12 VDC and improved visibility. · Video composite out

• Indoor/Outdoor; IP66; IK10

• SD card slot for on-camera storage • IP66; IK10 **MULTI-SENSOR SERIES Key Features Product Details** • 8 MP and 20 MP models Models: • Includes four separate camera modules (2 MP or 5 MP) V1008-WIR-180-1 V1020-WIR-180-1 • H.265/H.264 compression • Min. Illumination: up to 0.05 lux (color) • Temp: -40-131° F (-40-55° C) • True WDR • IR illumination; 90 ft (30 m) • Exposure settings for each module configured independently or globally The multi-sensor camera has four • FOV: 180° horizontal; 47° (8 MP)/32° (20 MP) vertical sensors that work together to provide Smart Encoding a detailed 180° panoramic view. • Audio and Alarm input/output • Powered by PoE+; 12 VDC; 24 VAC • SD card slot for on-camera storage • IK10; IP66

OUTDOOR HEMISPHERIC SERIES	Key Features	Product Details
V8360W	 6 MP and 12 MP models H.265/H.264 and M-JPEG compression Min. Illumination: up to 0.09 lux (color) Temp: -4-122° F (-20-50° C) True WDR Fisheye lens; 360° panorama at full HD IR illumination; 32 ft (10 m) Advanced Analytics 	Models: V8360W-6 V8360W-12
This camera provides a high-resolution, hemispherical view that eliminates blind spots and provides dewarping.	 Museum Search Smart Encoding Quad streaming Alarm and Audio input/output Powered by PoE; 12 VDC SD card slot for on-camera storage IP66; IK10 	
INDOOR DOME SERIES	Key Features	Product Details
* vicon	 2 MP and 4 MP models H.264/H.265 compression Min. Illumination: up to 0.08 lux (color) Temp: 14-104° F (-10-40° C) True WDR MFZ lens IR Illumination; 82 ft (25 m) Advanced Analytics 	Models: V802D-W312MIR V804D-W312MIR
These cameras combine excellent quality video in a cost-effective housing.	 Museum Search Smart Encoding Quad streaming Powered by PoE; 12 VDC Alarm and Audio input/output SD slot for on-camera storage 	
VANDAL MICRO DOME SERIES	Key Features	Product Details
∜ VICON	 2 MP and 4 MP models H.265/H.264 compression Min. Illumination: up to 0.005 lux (color) Temp: -31-140° F (-35-60° C) True WDR Fixed 2.8 mm lens/FOV (horizontal /vertical): 107.8°/56.7° (2 MP); 104.4°/54.40 (4 MP) Smart IR Illumination; 49 ft (15 m) 	Models: V842D-28IR V844D-W28IR
Designed for security installations that require a small form factor vandal dome.	 Museum Search Smart Encoding Two-way audio Powered by PoE; 12 VDC SD card slot for on-camera storage IP66; IK10 	

OUTDOOR TURRETS

V932D-IR-1/ V934D-IR



V9521D-312MIR V9541D-312MIR

The turret camera's innovative form factor provides ease of installation and adjustment.

Key Features

- 2MP and 4MP models
- H.264/H.265 compression
- Min. Illumination: up to 0.1 lux (color)
- Temp: 14-122° F (-10-50° C)
- WDR
- Fixed and MFZ lens models
- IR Illumination; 98 ft (30 m)
- Advanced Analytics
- Museum Search
- Smart Encoding
- Easy to install and adjust lens without opening
- Eliminates IR reflection
- Powered by PoE; 12 VDC
- IP66

Product Details

Models:

V932D-IR-1 V9521D-312MIR V934D-IR

V9541D-312MIR

VANDAL BULLET SERIES

Key Features

- 2 MP, 4 MP and 5 MP models
- H.264/H.265 compression
- Min. Illumination: up to 0.01 lux (color)
- Temp: -40-140° F (-40-60° C)
- MFZ lenses
- Smart IR Illumination; 98 ft (30 m)
- Museum Search
- Smart Encoding
- Alarm and Audio input/output
- High Dynamic Range and Starlight ultra-high sensitivity options
- Powered by PoE; 12 VDC; 24 VAC
- SD card slot for on-camera storage
- IP67

Product Details

Models:

V942B-W312MIR V942B-W310MIR-XW V942B-W310MIR-XS V944B-W312MIR V945B-W310MIR



with advanced Al-based analytics

These rugged outdoor cameras are

demanding security installments.

designed for performance in the most



These bullet cameras, with resolutions up to 4K, deliver sharper images, providing superior images in any environment.

Key Features

- 2 MP, 4 MP, 5 MP and 4K (8 MP) models
- H.264/H.265 and M-JPEG compression
- Min. Illumination: up to 0.03 lux (color)
- Temp: -4-122° F (-20-50° C)
- True WDR
- MFZ lens
- IR Illumination; 90 ft (30 m)
- Advanced Analytics
- Museum Search
- Quad streaming
- Audio and Alarm input/output
- Powered by PoE; 12 VDC
- Video composite out
- SD card slot for on-camera storage
- IP66; IK10

Product Details

Model:

V982B-W312MIR V984B-W312MIR V985B-W311MIR V988B-W311MIR

EXTENDED FOCAL LENGTH BULLET Key Features • 1080p resolution (1920 x 1080)

Product Details



• H.264 and MPEG-4 compression

- Min. Illumination: 0.35 lux (color)
- Temp: -22-122° F (-30-50° C)
- True WDR
- 10x MFZ lens
- IR illumination; 82 ft (25 m)
- Integral heater
- Museum Search
- Alarm and Audio input/output
- Powered by PoE+; 12 VDC
- SD card slot for camera storage
- IP66; IK10

Model:

V922B W551MIR-A1

This vandal bullet camera is designed for security installations that need a compact vandal resistant camera with a powerful 10x lens.

Key Features COST-EFFECTIVE BULLET SERIES

Product Details





• 2 MP and 4 MP models

• H.264/H.265 compression

• Min. Illumination: up to 0.1 lux (color)

• Temp: 14-122° F (-10-50° C)

• WDR

• Fixed and MFZ lens models

• IR Illumination; 98 ft (30 m)

Advanced Analytics

• Museum Search

Smart Encoding

• Small form factor

• Powered by PoE; 12 VDC

• IP66

V812B-312MIR V814B-312MIR

V812B-IR

V814B-IR

bullet housing.



These bullet cameras provide excellent quality video in a cost-effective

Models:

V812B-IR V812B-312MIR

V814B-IR

V814B-312MIR

THERMAL BULLET SERIES

Key Features

- 400 x 300 resolution
- H.265/H.264 and M-JPEG compression
- Temperature Detection/Display up to 8 areas
- 40 mK sensitivity
- Temp: -40-140° F (-40-60° C)
- Four lens choices: 15 mm, 25 mm, 35 mm, 50 mm
- 8 to 14 µm spectral range
- Advanced Analytics
- Smart Encoding
- Alarm and Audio input/output
- Powered by PoE; 12 VDC; 24 VAC
- SD card slot for on-camera storage
- IP66

Product Details

Models:

V1100B-THM-15MM V1100B-THM-25MM V1100B-THM-35MM V1100B-THM-50MM



The camera delivers thermal imaging that can be best used for perimeter and wide area protection.

Specialty Cameras / PTZ Dome Cameras

ROUGHNECK V-CELL-HD-B	Key Features	Product Details
	• 3 MP	Model:
	 H.264/MPEG-4/M-JPEG compression 	V-CELL-HD-B
	Min. Illumination: 0.0 lux (IR On)	
	• Temp: 32-140° F (0-60° C)	
	• WDR	
	• 2.3 mm fixed lens	
	• IR illumination; 65 ft (20 m)	
	Museum Search	
	 Integrated microphone and speaker 	
This heavy-duty, stainless steel high-	 Alarm input/output 	
security camera is designed specifically	Water-resistent enclosure	
for custodial suites and prison cells.	 Powered by PoE; 12 VDC 	
	• IK10	

CRUISER HD NETWORK PTZ DOME	Key Features	Product Details
≫ VICON	 1080P (1920×1080P) day/night camera H.265, H.264 and M-JPEG compression Min. Illumination: 0.35 lux (color) Temp: -4-140° F (-20-60° C) True WDR 23X optical zoom (5-117mm) IR illumination; 196 ft (60 m) Advanced Analytics 	Model: SN693V
This PTZ dome camera provides video surveillance over a wide area. The unique design eliminates distortion and allows viewing above the horizon.	 Museum Search Alarm and Audio input/output Powered by PoE+; 12 VDC SD card slot for on-camera storage IP66; IK10 	

CRUISER HD NETWORK PTZ DOME	Key Features	Product Details
	• 1080p (1920×1080p) day/night camera	Model:
	H.264 and M-JPEG compression	SN673V-B
	• Min. Illumination: 0.35 lux (color)	
•	• Temp: -4-140° F (-20-60° C)	
© AEON	True WDR	
	• 20x (4.7-94mm) optical zoom; 16x digital zoom	
	Museum Search	
	Alarm and Audio input/output	
	 Powered by PoE; 24 VAC; 12 VDC 	
his PTZ dome camera is designed	SD card slot for on-camera storage	
o provide crisp images in a compact package. It resolves quickly to preset	• IP66; IK10	
positions and focus.		

PTZ Dome Cameras (Cont'd)

RUGGED PTZ DOME	Key Features	Product Details
S Vocas	 3 MP resolution H.265, H.264 and M-JPEG compression Min. Illumination: 0.35 lux (color) Temp: -22-149° F (-30-65° C) True WDRI 36x optical zoom autoiris lens Synchronized IR illuminators; 1312 ft (400 m) Museum Search Advanced Analytics 	Model: SN683D-WIR
The rugged PTZ dome camera is designed for performance in demanding installations. It offers 36x zoom, providing greater telephoto distance, plus 3MP resolution.	 Quad streaming video Alarm and Audio input/output Powered by UPoE (PoE injector included); 12 VDC SD card slot for on-camera storage IP66; IK10 	

4K PTZ DOME	Key Features	Product Details
Designed for performance in the most demanding security installations, providing extreme detail for locations that require large area coverage, including campuses, airports, malls and hospitals.	 4K/8 MP resolution H.265/H.264 compression Min. Illumination: 0.75 lux (color) Temp: -22-131° F (-30-55° C) True WDR Varifocal 30x optical zoom autoiris lens Synchronized IR illuminators; 1312 ft (400 m) Museum Search Advanced Analytics Quad streaming video Alarm and Audio input/output Powered by UPoE (PoE injector included); 12 VDC SD card slot for on-camera storage IP66; IK10 	Model: SN688D-WIR

THERMAL SENSOR	Key Features	Product Details
3: VICON	 Thermal detection and tracking of intruders up to 400 m in a 360° panoramic view Integrated high-speed PTZ provides real-time tracking Geospatial tracking on localized maps Excellent performance regardless of lighting or weather conditions Dual inputs to VMS provide PTZ image and multi-screen customized thermal display One thermal unit can replace up to 8 fixed cameras 	Models: VTR-609 VTR-613 VTR-619 VTR-625
High-powered thermal sensor cameras provide 360° coverage to detect, identify and track intruders. Combined with the SN683D or SN688D PTZ, the result delivers situational awareness of any physical incursion.		

PTZ Dome Cameras (Cont'd) / HD Analog Cameras

Product Details IP PTZ SPEED DOME Key Features • 1080p resolution (1920 x 1080) Model: SN240D • H.264 and M-JPEG compression • Min. Illumination: 0.35 lux (color) • Temp: -58-149° F (-50-65° C) • True WDR • 30X optical zoom and 16X digital zoom • Museum Search • Max 380°/sec speed (preset) • Alarm and Audio input/output This IP PTZ dome camera is designed • Composite Video Out + RS485 to fit in a wide range of environments, • Powered by PoE; 12 VDC; 24 VAC providing superb sharpness and • IP66; IK10 excellent sensitivity.

AHD PTZ SPEED DOME	Key Features	Product Details
The AHD PTZ delivers HD quality video over coaxial cable, making it perfect for retrofit upgrades.	 2 MP resolution (AHD or HD-TVI) Min. Illumination: 0.35 lux (color) Temp: -58-149° F (-50-65° C) True WDR 30X optical zoom and 16X digital zoom 240 presets, 8 tours, 8 patterns Pan/Tilt speed: 380°/sec max Alarm input/output Composite Video Out + RS485 Powered by 12 VDC; 24 VAC IP66; IK10 	Model: V672-PTZ

HD ANALOG BOX	Key Features	Product Details
	• 2 MP (1080p; AHD/TVI)	Model:
	Supports AHD/TVI/CVBS	V672-W-NL
	Min. Illumination: 0.03 lux (color)	
# steen	• Temp: 14-122° F (-10-50° C)	
8 0.5	• True WDR	
	On-screen menus with innovative joystick control	
	make setup and operation easy	
High-resolution day/night box camera	Digital Noise Reduction	
that can accept a wide range of lens	• Defog	
options to suit any application.	• Provides C/CS lens mount and standard autoiris output	
approaches.	(Lens not included)	

HD Analog Cameras (Cont'd)

D ANALOG VANDAL DOME	Key Features	Product Details
	• 2 MP (1080p; AHD/TVI)	Model:
	 Supports AHD/TVI/CVBS 	V672D-W312MIR
	• Min. Illumination: 0.03 lux (color)	
*Vico _N	• Temp: 14-122° F (-10-50° C)	
(Commence)	• True WDR	
	 Varifocal lens; FOV: 119.9°-28.8° (horizontal) 	
· Property of the second	• IR Illumination; 98 ft (30 m)	
	HLC (High Light Compensation)	
	• Defog	
compact plastic dome housing	Digital Noise Reduction	
ncludes a fixed camera and motorized	On-screen menus with innovative joystick control	
arifocal lens.	 Accepts UTC (up the coax) protocol 	
	• IP66; IK10	

HD ANALOG VANDAL DOME	Key Features	Product Details
	• 2 MP (1080p; AHD/TVI)	Model:
	Supports AHD/TVI/CVBS	V672V-W312MIR-1
*	• Min. Illumination: 0.03 lux (color)	
*vicon	• Temp: 14-122° F (-10-50° C)	
- 6000	• True WDR	
	 Varifocal lens; FOV: 94.2°-26.2° (horiz) 	
	• IR Illumination; 98 ft (30 m)	
	HLC (High Light Compensation)	
	• Defog	
Compact, die-cast aluminum domed	Digital Noise Reduction	
housing incorporating a fixed camera	On-screen menus with innovative joystick control	
and motorized varifocal lens.	Accepts UTC (up the coax) protocol	
	• IP66; IK10	

HD ANALOG OUTDOOR BULLET	Key Features	Product Details
* vicon	 2 MP (1080p; AHD/TVI) Supports AHD/TVI/CVBS Min. Illumination: 0.03 lux (color) Temp: -20-122° F (-10-50° C) True WDR Varifocal lens; FOV: 91°-28° (horizontal) IR Illumination; 130 ft (40 m) HLC (High Light Compensation) Defog 	Model: V672B-W312MIR
Outdoor bullet camera offers a durable housing incorporating a fixed camera and motorized varifocal lens.	 Digital Noise Reduction On-screen menus with innovative joystick control make setup and operation easy Accepts UTC (up the coax) protocol IP66 	

Vicon's integrated product strategy means having innovative products at every layer of the security solutions stack — and within each layer — engineering them to work together seamlessly. With Vicon's high-performance security products that stand alone or work together, you can get the best fit for any organization.

Vicon's trusted products and solutions are installed around the globe in over 40,000 companies in a variety of vertical markets.

For more information about Vicon visit our website: vicon-security.com



Corporate Headquarters

VICON INDUSTRIES

Tel: 631.952.2288

Toll-Free Sales: +1.800.645.9116 Email: sales@vicon-security.com

European Headquarters

VICON INDUSTRIES LIMITED

Tel: +44 1489 566300 Sales: +44 1489 566310

Email: uksales@vicon-security.com









vicon-security.com • #viconsecurity