



Fixed Network Camera

2.0 Megapixel / H.264 / 720p Real-Time

- 1/3" Progressive Scan CMOS image sensor
- 15 fps @ 1600 x 1200 (UXGA),
30 fps @ 1280 x 720 (WXGA / 720p)
- H.264/MJPEG dual codec
- Enhanced imaging with 3D DNR
- Digital I/O for external sensor and alarm
- PoE (Power over Ethernet)
- True day/night (ICR)
- 2-way audio support
- Micro SD card support up to 32GB (not included)



Lens not included

Bracket not included

Specifications

Camera

Sensor	1/3" Progressive Scan CMOS
Scan Method	Progressive
Lens	C/CS-Mount (not included)
Maximum Resolution	1600 x 1200
Minimum Illumination	C/L : 0.1Lux (AT 30 IRE, F1.0), B/W : 0.02Lux (AT 30 IRE F1.0)
Day/Night	True Day/Night (ICR)
Wide Dynamic	No
SNR (max)	42.3db
Digital Noise Reduction	Auto (3D-DNR)
White Balance	Auto
Gain Control	High/Middle/Low, 3 steps selection
Flicker Control	Off/50 Hz/60 Hz, 3 steps selection
Backlight Compensation	On/Off
Electronic Shutter	Auto/Slow Shutter (2x~16x / 5 steps selection)
Iris Control	Manual
HLC (High Light Compensation)	N/A

Video

Video Compression Format	H.264 (MPEG-4Part 10/AVC)/MJPEG,Dual codec
Video Frame Rate	H.264 : 2M (1600x1200@15fps) 720p (1280x720@30fps) MJPEG : 2M (1600x1200@15fps) 720p (1280x720@15fps)
Bitrate Control	CBR and VBR, 128kbps ~ 4Mbps
Multi-streams	Dual streaming, Multiple profiles 1280x720 H.264@30fps/640x352 H.264(Sub)@30fps/1280x720 MJPEG@15fps 1600x1200 H.264@15fps/640x480 H.264(Sub)@15fps/1600x1200 MJPEG@15fps
Digital Zoom (PC Side)	1/4x, 1/3x, 1/2x, 1x, 2x, 4x
Image Rotation	Mirror, Flip, Rotate 180°

Audio

Audio Streaming	Two Way
Compression	AMR, G.711 @ 64kbps, G.726 @ 32kbps / Configure bit rate

Intelligent Video

I/A	Motion Detection / Tamper Detection / Privacy Mask
-----	--

System Requirements

Browser	Internet Explorer 6.0 or above, Firefox, Chrome, Safari
---------	---

Application Software
OS Supported

VMS Application Software
Microsoft Windows 2000, XP, Vista, Windows 7

I/O and Connectors

LAN
Audio
Alarm I/O
Serial Port
Factory Default

1 x RJ-45 Ethernet Connector
1 x Audio in, 1 x Audio out
1 x Alarm in, 1 x Alarm out
RS-485 (2 pin)
1 x Reset Button

General

Storage
Power Input
Power Consumption
Operating Environment

1 x Micro SD Card (SDHC up to 32GB)
DC12V / PoE
3.6 W
Operating temperature : 14° F ~ 122°F
Storage temperature : -4°F ~ 140°F
Operating humidity : 0% ~ 95% Non-condensing
6.22" (L) x 2.56" (W) x 2.31" (H)
0.84 lbs (without lens)
CE, FCC, Class A, RoHS
3 years

Dimensions

Weight
Safety Certifications
Warranty

Network

Streaming Protocols


RTSP/RTP/UDP/RTSP/RTP/TCP/RTSP/RTP/
HTTP tunneling, LAN Multicast, Multipart-JPEG
IPv4, HTTP, UDP, TCP, ICMP, IGMP, ARP, DHCP, NTP, SMTP,
FTP, SAMBA, UPnP, PPPoE, DNS, DDNS, RTSP, RTP, RTCP, ONVIF

Supported Protocols



Fixed Network Camera

Product Diagram:



Features:


2.0 Megapixel Resolution

Cover more space or zoom in for more detail



3D Digital Noise Reduction (3D DNR)

Filter out noise even in low-light conditions



Progressive Scan

Delivers faster transmission speeds and sharper details



Suggested Accessories:

3S Light Duty Security
Camera Mounting Bracket



Member of:



Product Certification:

